

## Scissor elevating platform, mobile with double scissor model HX-D

Capacity 350 - 700 kg,  
platform height max. 1500 mm

For the independant lifting and supplying of light up to medium loads within a warehouse environment.

### Features

- Hydraulic lifting of the load with foot pedal.
- Lowering speed can be finely metered for sensitive lowering of the load.
- Ergonomic handlebar for easy operation.
- Steering roller with parking brake for safe parking of the hand stacker.
- Robust construction with hard chromium plated piston and pressure relief valve.
- According to EN 1570, prEN 1757-4.



### Technical data model HX-D

Model	HX-D 0350	HX-D 700
Art.-No.	034600024	040047506
Capacity, kg	350	700
Platform height max. $h_3 + h_{13}$ , mm	1300	1500
Platform height min. $h_{13}$ , mm	370	445
Stroke $h_3$ , mm	930	1055
Lifting height per pump stroke, mm	21	11
Overall height $h_1$ , mm	965	1015
Overall length $L_1$ , mm	1140	1480
Overall width $b_1$ , mm	500	610
Platform length $P_1$ , mm	910	1220
Platform width $P_2$ , mm	500	610
Tyre type*	PUR/PUR	PUR/PUR
Load rollers, mm	128 x 40	128 x 40
Number of wheels/load rollers	2/2	2/2
Weight, kg	136	195

\*PA... Polyamide, PUR... Polyurethane, VG... Solid rubber

